





"PURE GOODNESS,
POWERED BY INNOVATIONS"








DATA PROCESSING UNIT (DPU)





EKOMILK Ultra Pro (Double sensor)



Compact and light weight design milk analyzer. Very small quantity of milk sample required for testing with no added chemicals.

Features

- Fastest Operations.
- Cost effective operations.
- Easy to clean and maintain.
- Very Low power consumption.
- RS 232 Interface.
- 1 Year Warrenty.

Measuring Parameters

Fat	From 0.5% to 12% with accuracy of ± 0.1%
Solid not fat (SNF)	From 6% to 12% with accuracy ± 0.2%
Protein	From 2% to 6% with accuracy ± 0.2%
Lactose	From 0.5% to 7% with accuracy ± 0.2%
Added water to Milk	From 0% to 60% with accuracy ± 5%
Average speed	120 samples/hour
Repeatability	0/-0.03 % for fat, ± 0.05% for SNF, ± 0.75% for added water





Accesories

• RS 232 Cable	- 01 Nos
AC Power Cable with Plug top	- 01 Nos
 Battery Power Cable 	- 01 Nos
• 200ml Daily cleaning Solution	- 01 Nos
• 200ml Weekly cleaning Solution	n- 01 Nos
• 200ml Power cleaning Solution	- 01 Nos
 Measuring Mug 	- 02 Nos
 Operating Manual 	- 01 Nos

(Exclusive Representative in India of Eko Milk Ultra Pro Analyzers)

DATA PROCESSING UNIT (DPU)



Features:

- Micro-Controller based embedded design.
- RFID for customers identification (Optional).
- Direct interface.
- Milk Analyzer to get Date, Weight (Kg/Ltr),
- FAT%, SNF%, Added water%.
- DPU With In-bult Keyboard.
- In-built Thermal printer.
- Data transfer through USB Flash drive/GSM/GPRS.
- 2 Rate chart storage facility.
- Print/view shift report with weighted average.
- Store date up-to 12 months.
- Available in different models and as per customers requirements.



Also Available Android Based



Technical Specifications:

Display: 95mmx55mm Jumbo LCD Display

Printer: Thermal Printed-2.0" Panel Mounted

RS-232 Input Ports: 1. Milk Analyzer

2. External Weighing Scale

RS-232 Output Ports: 1. Remote Display

2. 2G/3G/4G Modem

USB Ports: 1. USB Keyboards interface

2. Pen Drive interface

Functional Specifications:

Data Storage	-	1000 Customers per shift
Weighing Scale	-	Auto Tare, Ltr. conversion & Adjustable Decimal Point
		Auto configurable Baud Rate
Milk Collection Type	-	Code base or FAT limit base
Cumulative Total	-	Cumulative total in slip, 10 Days/15 Days/Monthly
Protection	-	Password Protection at various stages
Rate Chart	-	Auto generation, Based on FAT, FAT-SNF, FAT-CLR
		Import and Export to Pen drive
Data and Reports	-	.csv format Export to Pen drive
Data transfer	-	Farmers data Transfer to Pen drive via USB port
		Transfer to Remote server through Mobile/GSM/GPRS





STIPL Digital Ultrasonic Stirrer



A Hygienic and powerful supportive equipment for removing air bubbles from the milk samples, before analysis. It is cost effective and easy method that facilitates industries grade noninterrupted operations.

Function/Features

- Soft start
- LED Display
- Push Button Operational control
- Minimum time setting: 10 secs
- Maximum time setting: 60 secs
- Time increment steps: 01 sec
- Time display 2 nos. 7 segment LED display
- Input voltage: 170 to 290 AC volt.
- Input voltage: 10.5 to 16 volts DC

(upto 30 volts DC)

Technical Specifications:

Input voltage: 170 to 290 AC volt.

Input Frequency: 45 to 55 Hz.

Input power: 32 VA max.



Available In:

- Stainless Steel (304)
- MS Powder Coated



DC Operations:

Input voltage: 10.5 to 16 DC volt.

Input current: 22 amps max.

Reversed Battery protection

External Displays



Remote Display

- Bright LED Display
- To Display-Code ,Milk Type, Fat%, SNF%, Weight, Rate and Amount.



Analyzer Display

- Bright LED Display
- To Display-Fat%, SNF%, Degree and Added Water.

SHIV TRADERS INSTRUMENTS PVT. LTD.

Contact Us:

- +91 0233 2314172, 9370954458
- sales@shivtradersinstruments.com
 salesho@shivtradersinstruments.com
- www.shivtradersinstruments.com
- "Shiv Bhavan", Plot No.66, Raj Nagar,
 East of Chintamani Nagar,
 Madhav Nagar Road, Sangli 416 416.
 Maharashtra, India